



JPG



YES
YOUR EQUIPMENT SERVICES

JACKET PILE GRIPPERS





YES
YOUR EQUIPMENT SERVICES

DESIGN

- Sizeable to any pile diameter
- Balanced design in number of cylinders versus gripping capacity
- Ring height sufficient to limit heat affected zone close to cylinder fittings and hydraulics during installation (welding) at yard
- Compliant to standards and 3rd party Design Approval (DAD)

FEATURES

- Tailored to jacket design and offshore installation methodology, allowing for:
 - Clearance for hammer and drilling equipment;
 - The installation (and clearance) of levelling equipment;
 - The placement of the grout.

OPERATION

- Hydraulically operated with fail-safe
- Operation redundancy – from surface and/or ROV-panel
- Ability to re-grip by dual-acting cylinders

INSTALLATION

- FAT and packed ready for shipment at fabrication site
- Transport can be arranged for
- Optional on-site installation support, commissioning and SAT

Examples / Proposals



HVDC-Platform Centre Manche

2GW-Platform TENNET/AMPRION

Project Input

Centre Manche

CASE – OFFSHORE SUBSTATION


- 6 legs
- 10 pile sleeves
- Jacket weight 5,250T excl. piles
- Pile diameter 2,438mm (96")
- Pile sleeve diameter 2,890mm

GRIPPING SCENARIOS

Scenario	Pile Grippers (#)	Max Horizontal Force $F_{h,max}$ (t)	Max. Vertical Force $F_{v,max}$ (t)
Pile gripper per pile sleeve	10	242.64	-993.96
Pile gripper per leg	6	298.43	-1043.39



YES
YOUR EQUIPMENT SERVICES




Design – Centre Manche

PILE GRIPPER – STRUCTURE

- Scenario one (1) gripper per leg (6 total)
- Eight (8) hydraulic jacks for sufficient clamping force
- No vertical adjustment capability
- Funnel and sleeves are not part of scope
- Grippers to be installed (welded) upon jacket at yard
- Ring height sufficient to limit heat affected zone during installation (welding) close to hydraulics and fitting of jacks

DESIGN ALLOWS FOR:

- Clearance for hammer and drilling equipment so underwater cutting of piles is avoided later,
- The installation (and clearance) of levelling equipment,
- The placement of the grout.







Operation – Centre Manche

PILE GRIPPER – HYDRAULICS

- Double acting cylinders
- Rigid piping installed on gripper ring to feed jacks

PILE GRIPPER – OPERATION

- Base case is one (1) ROV-panel and hot stab per gripper
- Connecting frame on ring to bolt on ROV-Panel
- Standard operating pressure of 250 bar is assumed
- Stab and receptacle have $\varnothing 35$ hydraulic bores, when used on 8 jacking cylinders act gradually
- Control from surface is optional



EPC Bid – Centre Manche



DETAILS

- **2.438 mm Hydraulic pile gripper**
- **S355J2 steel**
- **8* Ø250 mm * 200mm stroke double-acting hydraulic cylinders**
- **Hydraulic piping for connections between cylinders and ROV panel**
- **Necessary NAS 6 Biodegradable hydraulic oil BIOVESTA 46**
- **Surface treatment SA 21/2 Blasting + 150mm epoxy**
- **Assembly and factory test**
- **Load testing TBD with client**
- **Packaging**

SERVICES


- **On-site support for fitting and commissioning + SAT on day rate**
- **Class certification on a cost+15% basis**
- **Transport from fabrication site to construction yard on a cost+15%**

Project Input

2GW Platform


CASE – 2GW OFFSHORE SUBSTATION

- Five (5) platforms
- Eight (8) Jacket Pile Grippers per jacket
- Each Jacket Pile Gripper has 1,500T gripping capacity
- Jacket weight 12,850T excl. piles
- Pile diameter OD 2,743mm
- Pile sleeve diameter & thickness 3,125x50mm



SINGLE PILE CLUSTER ISOMETRIC VIEW

Source: Dragados Offshore, S.A for BalWin1 and BalWin2






Design – 2GW Platform

PILE GRIPPER – STRUCTURE

- Eight (8) Jacket Pile Grippers per jacket
- Eight (8) hydraulic jacks for sufficient clamping force (8*1,500T)
- No vertical adjustment capability
- Funnel and sleeves are not part of scope
- Grippers to be installed (welded) upon jacket at yard
- Ring height sufficient to limit heat affected zone during installation (welding) close to hydraulics and fitting of jacks

DESIGN ALLOWS FOR:

- Clearance for hammer and drilling equipment so underwater cutting of piles is avoided later,
- The installation (and clearance) of levelling equipment,
- The placement of the grout.



Operation – 2GW Platform






PILE GRIPPER – HYDRAULICS

- Double acting cylinders
- Rigid piping installed on gripper ring to feed jacks

PILE GRIPPER – OPERATION

- Base case is one (1) ROV-panel and hot stab per gripper
- Connecting frame on ring to bolt on ROV-Panel
- Standard operating pressure of 250 bar is assumed
- Stab and receptacle have $\varnothing 35$ hydraulic bores, when used on 8 jacking cylinders act gradually
- Control from surface is optional



EPC Bid – 2GW Platform



DETAILS

- **3,125 mm Hydraulic Jacket Pile Gripper**
- **Design / 3 modelling / 2d drawings / FEM and DNV Design Approval**
- **IOM Manuals and MRB package**
- **S420 steel**
- **8* double-acting hydraulic cylinders**
- **ROV-Panel**
- **Hydraulic piping for connections between cylinders and ROV panel**
- **Rotating hoist rings + Bolts and washers**
- **Necessary NAS 6 Biodegradable hydraulic oil BIOVESTA 46**
- **Surface treatment and Sigmacover380 DFT=125µm+Sigmacover456 DFT=125µm (colour TBD)**
- **Assembly and factory test**
- **Packaging**

SERVICES

- **On-site support for fitting and commissioning + SAT against cost+15%**
- **Transport from fabrication site to construction yard against cost+15%**
 - **Batched transport possible 5*8 dependent delivery schedule**
- **Load-test and number of tests (test interval) TBD**



YES

YOUR EQUIPMENT SERVICES

Your Equipment Services B.V.

W www.yes-equipment.com | E info@yes-equipment.com | T +31 6 5389 9270